

REVERSIBLE TORQUE WRENCHES

From
1/4" to 1"



1. The ratchet gear is made in Cr-V for maximum strength.

2. Wider range with larger clamping range, reaching from 2,5Nm to 3000N.

3. Increased number of teeth on the gear 45, instead of 32, in order to reduce the required minimum angle of rotation from 11 ° to 8 °.

4. Double scale window, larger and more visible for having torque adjustment more precise and accurate. The scale in units Nm, lb.ft and Lb.in to square drive 1/4 ".

5. Ergonomic non slip **BMAT** handle.


6. Push type locking system.

7. Reversible torque wrench with a gear lever.

8. Mirror polished chrome plating.

9. Individual carrying case.

REVERSIBLE TORQUE WRENCH



COD.	AF inch	N.m	Lb.ft	Lb.in	L (mm)	A (mm)	B (mm)	C (mm)	D (mm)	Kg	
62951		2.5-12		20-105							
62952	1/4	4-20		30-180	290	28	30	19		0,8	
65871		-	-	35-180	230						
62965		6-30		50-250	320	37	40			0,9	
65872	3/8	-		120-450	380	40	44			1,3	
62953		25-125	20-90	-			40				
57686		10-70	-	100-600	440	38	41			0,9	
62954		25-125	20-90	-				25		1,3	
65873		-	-	350-1800	520				38	1,4	1
62963	1/2	40-200	30-150	-	460		44				
62968		65-335	50-250	-	520	40				1,5	
65918		-	-	1000-3000							
62983		80-400	60-300	-	750					1,9	
62969	3/4	160-800	120-600	-	1040	60	66	39		8,6	
62976		200-1000	150-750	-							
62977	1	300-1500	200-1100	-						12	
62978		400-2000	300-1500	-	1250	72	82	40		12,2	
62979		600-3000	400-2200	-						13,2	



12M | Repair kit available

TECHNICAL SPECIFICATION

Accuracy	3%
Calibration certificate	●
Reversible	●
Teeth	45
Individual case	●

TECHNICAL SPECIFICATION

MATERIAL	Body	Steel
	Handle	TPR (Black and red)
HARDNESS	Square drive	39 HRC.

EXTENSION BAR FOR TORQUE WRENCH

COD.	L (mm)		Valid for	Kg	
56497	1100	38	62977, 62978, 56494, 56495	3,4	1
56498		40,5	62979, 56496	4,7	

