

TORQUE WRENCHES RF WIRELESS

Digital torque wrenches with angle measurement and RF wireless data communication **EGATORAK** EGA Master's digital torque wrenches with angle measurement and RF wireless data communication are the most advanced tools in their class, providing superior performance for the most demanding tasks in top-tier work environments, such as the aerospace or railway industry.

**WITH
ANGLE
MEASUREMENT**



**With
rectangular
connection
(24x32/27x36)**



1. Data communication with our new RF technology provides automation and ease of work control.
2. Fully wireless transmission. Information is delivered immediately to the central software.
3. Central management software for PC included.
4. The receiver can process up to 10 torque wrenches simultaneously.
5. Easy-to-use system for straightforward and intuitive work.
6. With a universal rectangular connection and a wide range of interchangeable heads available.
7. Sound and light warning system with progressive lighting of LEDs as the preset value is approached.
8. The communication distance between the receiver and the wrench can be, under optimal conditions, up to 100m*.
9. 24-hour web-based calibration.
10. Mirror-polished chrome finish.
11. Individual portable case.

*May be reduced depending on the environment in which measurements are taken and on objects, especially metallic ones, that are between the receiver and the wrench.

EGATORK

LONG SERIES



COD.	mm	N.m	Lb.ft	✓	L (mm)	A (mm)	Kg	
59131	24x32	50-1000	36-737	1-360°	1730	38	13	1
59132	27x36	100-2000	74-1475		1740		14	

12M



COD.	CW Accuracy (Right-handed)	CCW Accuracy (Left-handed)	Resolution	Data memory	Data communication to the computer
59131	±2,5%	±3,5%	1 N.m / 1 Lb.ft / 1°	2000	RF WIRELESS
59132					

TECHNICAL SPECIFICATIONS

Calibration certificate	•
Alert system	Light and sound alarm
Units of measurement	N.m / Lb.Ft / °
Web-based calibration	•
Batteries	AA x 2
Battery life	110 h
Standby battery life	1 year
Operating temperature	-10 °C ~ 60 °C
Storage temperature	-20 °C ~ 70 °C
Maximum communication distance between receiver and wrench	100 m (The distance may be reduced depending on the environment.)
Frequency band	ISM 433 MHz
Connection dimensions	
	59131 24 x 32 mm
	59132 27 x 36 mm

RECEIVER

COD.	Valid for	Kg	
58770	58764, 58765, 58766, 59130, 59131, 59132, 58767, 58768, 58769, 59133, 59134, 59135	1,4	1

12M

TECHNICAL SPECIFICATIONS

CD with the programs for data communication	•
Frequency band	ISM 433MHz



EGATORK

INTERCHANGEABLE HEADS

OPEN HEADS

MM

COD.	AF mm	mm
68242	20	
68243	24	
68244	27	
68245	28	
68246	30	
68247	32	
68248	34	
68249	36	
68250	38	
68251	41	24 x 32
68252	45	
68253	46	
68254	50	
68255	55	
68256	60	
68257	65	
68258	67	
68259	70	
57097	80	



INCH

COD.	AF inch	mm
56484	5/8	
56485	3/4	
56486	7/8	24 x 32
56487	1.1/8	
56488	1.3/4	
56489	2.1/4	



RATCHET HEADS

COD.	AF inch	Teeth	mm
68240	3/4	45	24 x 32
68241	1		



BOX HEADS

MM

COD.	AF mm	mm
68260	24	
68261	30	
68262	32	
68263	34	
68264	36	
68265	38	
68266	41	24 x 32
68267	46	
68268	50	
68269	55	
68270	60	
68271	65	
68272	70	



BOX OPEN HEADS

MM

COD.	AF mm	mm
68273	19	
68274	30	
68275	32	
68276	36	24 x 32
68277	38	
68278	50	
68279	70	



INCH

COD.	AF inch	mm
56490	15/16	24 x 32
56491	1.1/8	



ADAPTERS

COD.	AF inch	mm	L (mm)	g
59116	24 x 32	14 x 18	90	500
59119		27 x 36	105	1250



EGATORK

INTERCHANGEABLE HEADS

OPEN HEADS

MM

COD.	AF mm	mm
56510	41	27 x 36
56511	46	
56512	50	
56513	55	
56514	60	
56515	61	
56516	65	
56517	70	
56518	75	
56519	80	
56520	90	
56521	95	



BOX OPEN HEADS

MM

COD.	AF mm	mm
56536	30	27 x 36
56537	32	
56538	36	



RATCHET HEADS

COD.	AF inch	Dientes / Teeth / Dents	mm
56539	1	45	27 x 36



BOX HEADS

MM

COD.	AF mm	mm
56522	30	27 x 36
56523	32	
56524	34	
56525	36	
56526	38	
56527	41	
56528	46	
56529	50	
56530	55	
56531	60	
56532	65	
56533	70	
56534	75	
56535	80	



ADAPTERS

COD.	AF inch	mm	L (mm)	g
59118	27 x 36	24 x 32	105	1150

